

IRU1300

Cradle for PHL1300



+ Specifications

Communication

- RS232: Baudrate 1200 bps - 115.2 kbps, half duplex RS232, D Sub 9P F connector
- RS485: Half duplex RS485, 6 pins modular plug connector

Power

- Voltage requirement: 9V
- Battery charging time: Ca. 8 hours

Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 70 °C / -4 to 158 °F
- Humidity in operation: 30 - 85% (non-condensing)
- Humidity in storage: 30 - 90% (non-condensing)

Physical

- Dimensions (w x h x d):
78 x 75 x 134 mm / 3.07 x 2.95 x 5.28 in
- Weight body: Ca. 150 g / 5.3 oz
- Case: ABS, Grey

Regulatory & Safety

- Product compliance: EN 55022, EN 55024

Sold separately

- USB cable
- RS232 cable
- Power supply 230V/4.5A, 50 Hz, 9V/0.5A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM